B1033200-CD-1510-004 Rev 0 Carriageway Central Reserve Carriageway (PC) 600(s)(Cat5e) EDP (PC) CABLING TO OTHER
CO-LOCATED TSE
IF REQUIRED Lane Configuration varies at different locations Notes ယ္ 5 4 Ņ B1033200-CD-1510-004 It is the responsibility of the Contractor to incorporate the outline guidance provided into a design conforming to all applicable regulations, requirements and designed by the company in accordance with drawing B1033200-CD-1510-007 and the NDX drawing series. A standardised cabinet layout design shall be used at TSE sites berdeen Western Peripheral Rabalmedie-Tipperty Equipment contained within the 600 omitted for clarity arawing is not to be used in whole or part other than for the intended use and project as defined on this drawing. Refer to the contract for full and conditions. Legend This drawing is a typical arrangement providing outline guidance only Site layout to conform to NDX 600(s) cabinet internal layout to be drawing series requirements including hardstanding and associated paths, steps and handrails as needed 600(s) (PC) TYPICAL VMS LAYOUT & CONNECTION DETAIL FOR INFORMATION DO NOT SCAL JACOBS:

Variable Message Sign (Offset-T or Cantilever)

O ?

Φ

Termination Pillar

Power Cable

Traffic Equipment Distribution Pillar

Type 600 Cabinet

Cat5e Cable